

Rolled Shell 3.3" Motors !!

Open Construction - 1550 RPM

Part #	Amps	Volts	H.P.	Rot.	Shaft	Body	Feature	Comment	Fig.
R91125	0.50	208/230	1/12	CW	2.63"x5/16"	3.66	PSC/Cap.Inc	9720A, D1125, 41125	1
R90015	0.70	115	1/70	CW	2.24"x1/4"	2.14	4 Studs front & rear	15, D121, 40121, 3M539	2
R90014	0.70	115	1/70	CCW	2.24"x1/4"	2.14	4 Studs front & rear	14, D120, 40120, 3M538	2
R90575	0.89	230	1/20	CW	2.48"x5/16"	2.75	2 Pin plug	575, D1103, 41195,	3
R90189	0.90	230	1/20	CW	2.24"x5/16"	2.75	4 Studs front & rear	D189, 40189	2
R90188	0.90	230	1/20	CCW	2.24"x5/16"	2.75	4 Studs front & rear	D188, 40188	2
R90027	1.10	115	1/40	CW	2.24"x5/16"	2.44	4 Studs front & rear	27, D127, 40127, 3M544	2
R90026	1.10	115	1/40	CCW	2.24"x5/16"	2.44	4 Studs front & rear	26, D126, 40126, 3M543	2
R90573	1.20	208/230	1/15	CCW	3.03"x5/16"	3.50	2 Pin plug	573A, D1126, 45008T	3
R90752	1.30	120	1/40	CW	1.3"x1/4"	2.15	1500 RPM	40752	3
R90514	1.30	115	1/30	CCW	2.38"x5/16"	2.69	4 Studs front & rear	D514, 40514	2
R90031	1.60	115	1/25	CW	2.57"x5/16"	2.75	4 Studs front & rear	31, 40031	2
R90030	1.60	115	1/25	CCW	2.57"x5/16"	2.75	4 Studs front & rear	30, 40030	2
R90572	1.80	115	1/15	CCW	3.03"x5/16"	3.00	2 Pin Plug	572A, D1124, 45008S	3
R90133	1.80	115	1/20	CW	2.24"x5/16"	2.75	4 studs front & rear	D133, 40133	2
R90132	1.80	115	1/20	CCW	2.24"x5/16"	2.75	4 studs front & rear	D132, 40132, 3M547	2
R90574	1.90	115	1/20	CW	2.48"x5/16"	2.75	2 Pin plug	574, D1101, 41194	3
R90672	2.10	115 208/230	1/15	CCW	2.24"x5/16"	5.00	Mechanical Duty	672, 81672	4
R90671	2.10	115 208/230	1/15	CW	2.24"x5/16"	5.00	Mechanical Duty	671, 81671	4



Fig. 1



Fig. 2



Fig. 3



Fig. 4

Totally Enclosed - 1550 RPM

Part #	Amps	Volts	H.P.	Rot.	Shaft	Body	Feature	Comment	Fig.
R90021	0.80	115	1/50	CW	2.24"x1/4"	2.44	4 studs front & rear	21, D125, 40125, 3M661	5
R90020	0.80	115	1/50	CCW	2.24"x1/4"	2.44	4 studs front & rear	20, D124, 40124, 3M554	5
R90017	0.60	115	1/80	CW	2.24"x1/4"	2.14	4 studs front & rear	17, D123, 40123	5
R90016	0.60	115	1/80	CCW	2.24"x1/4"	2.14	4 studs front & rear	16, D122, 40122	5
R91189	1.60	115 208/230	1/20	CCW	1.65"x5/16"	3.15	3 ears	D1189, 41189	6



Fig. 5

Totally Enclosed - 3000 RPM

Part #	Amps	Volts	HP	Rot	Shaft	Body	Feature	Comment	Fig
R90402	0.75	115	1/60	CCW	1.73"x1/4"	2.36	4 studs front & rear	D402, 40402	5
R90616	0.75	115	1/70	CW	0.96"x1/4"	2.28	Cord & plug	82500	5



Fig. 6