

# RLINE

## 53-D-340

### REFRIGERANT LEAK DETECTION

#### FEATURES

- Designed for leak sensing requirements of R22, R410a & R134a but will also detect all commercially available HCFC, HFC, CFC as well as the newer replacement blend refrigerants.
- The most sensitive hand held leak detector on the market when adjusted to MAX mode.
- Adjustable sensitivity levels.
- No false alarms.
- No calibration required.
- Long life heated sensor.
- Audio volume control.
- Low battery indicator.
- Finds leaks in contaminated areas.
- Includes holster with belt clip.

#### SPECIFICATIONS

Alarm Sensitivity:	0.05 oz/yr. (R134a), 0.025 oz/yr. (R22)
Sensitivity:	Exceeds SAE standard J1627.
Power:	4 AA batteries
Battery Life:	8 to 10 continuous hrs with low battery indicator.
Warm Up:	Less than 30 seconds.
Operating Temperature:	0°C to 40°C (-32°F to 104°F)
Probe Length:	42 cm (16.5")
Total Reach:	61 cm (24")
Weight:	0.35 kg (12.3 oz.)
Warranty:	2 years.

#### APPLICATIONS

- Motor vehicle A/C
- Centrifugal chillers
- Refrigerant transport
- Industrial process refrigeration.
- Industrial process air conditioning
- Ice skating rinks
- Cold storage warehouses
- Heat transfer systems
- Household refrigerators, freezers & A/C
- Reciprocating & screw chillers
- Retail food refrigeration
- Ice machines
- Vending machines
- Water coolers
- Refrigerated transport

