

DiversiWhips

Product

Liquid-tight Flexible Conduit

Purpose

The DiversiWhips are a labor saving convenience kit for A/C unit hookup. They can also be used for heat pumps, refrigeration, hot tubs, swimming pools, and outdoor lighting.

Features

- Easy to use.
- Simple to install.
- Three distinct wire colors for ease of hook-up

Specifications

- Liquid-tight construction/Weatherproof
- UV Resistant: Titanium Dioxide and Carbon Black act as a UV inhibitor
- 1 straight and 1 90 degree metallic or non-metallic connector
- 90 degree connector is removable for straight connectors (Second straight connector not included)
- UL and cUL Listed
- Max Temp - 75°C
- Number of Conductors - 3
- Number of Connections - 2
- Connection Type - Male Pipe Thread
- Warranty - 1 year

• Printed on Conduit: DIVERSITECH NON-METALLIC LIQUID-TIGHT CONDUIT 75 C 1/2 INCH FNMC-8 OUTDOOR DIRECT BURIAL 80 DEGREES C DRY 60 DEGREES C WET, 70 DEGREES C OIL RESC UL US LISTED 3FF0

Wire Length extending from ends: 6.5 inches ± 0.5 inch

General Characteristics

Model	Wire Size	Conduit Size	Connector Type	Length
6-12-4	#10 THHN	1/2 INCH	Metallic	4 FT
6-12-4-NM	#10 THHN	1/2 INCH	Non-Metallic	4 FT
6-12-6	#10 THHN	1/2 INCH	Metallic	6 FT
6-12-6NM	#10 THHN	1/2 INCH	Non-Metallic	6 FT
6-34-4	#8 THHN	3/4 INCH	Metallic	4 FT
6-34-4NM	#8 THHN	3/4 INCH	Non-Metallic	4 FT
6-34-6	#8 THHN	3/4 INCH	Metallic	6 FT
6-34-6NM	#8 THHN	3/4 INCH	Non-Metallic	6 FT
6-34-8	#8 THHN	3/4 INCH	Metallic	8 FT
6-34-8NM	#8 THHN	3/4 INCH	Non-Metallic	8 FT

