

## Flexible Refrigerant Lines

**Product** Flexible Refrigerant Lines

**Purpose** The DiversiTech Flex-Line Connectors allow a kink-free connection from the mini-split wall unit to the refrigerant lines for easier and faster installation while also helping to reduce or eliminate vibration transmission.

- Features**
- Quick and easy installation
  - Kink-free
  - Braided stainless steel jacket
  - Corrugated stainless steel inner tube
  - For use with R410a and R22 refrigerants
  - 800 PSI operating pressure rating

- General Specifications**
- Conforms to UL STD 207 and 1963
  - Certified to CSA STD C22.2 NO 120
  - NOT FOR USE WITH AMMONIA
  - Warranty: 1 year

### General Characteristics

Line Set	Length	Type	Copper Wall Thickness	Burst Pressure Minimum	Static Bend Radius Min	Weight
FRL14	36 in	1/4 in tubing	0.03 in	4000 PSI	0.9 in	0.5 lbs
FRL14-F	36 in	1/4 in tubing with flare	0.03 in	4000 PSI	0.9 in	0.5 lbs
FRL38	36 in	3/8 in tubing	0.032 in	4000 PSI	1.0 in	0.7 lbs
FRL38-F	36 in	3/8 in tubing with flare	0.032 in	4000 PSI	1.0 in	0.7 lbs
FRL12	36 in	1/2 in tubing	0.047 in	4000 PSI	1.2 in	0.8 lbs
FRL12-F	36 in	1/2 in tubing with flare	0.047 in	4000 PSI	1.2 in	0.8 lbs
FRL58	36 in	5/8 in tubing	0.053 in	4000 PSI	1.4 in	1.15 lbs
FRL58-F	36 in	5/8 in tubing with flare	0.053 in	4000 PSI	1.4 in	1.15 lbs



**FRL12**



**FRL14-F**

## Flexible Refrigerant Lines

