

Dual Element Fuses

Product

Dual Element Fuses

Purpose

Provides time delay for temporary over-current conditions and motor running protection for heating and air conditioning equipment. Eliminates unnecessary maintenance from harmless overloads.

Features

- Current Limiting Fuses
- Time Delay

Technical Specifications

- Total Lifetime Amps: 200,000
- UL Class RK-5
- Standard for Safety 198E



General Characteristics

Model	Voltage	Amps	UPC	Order Multiple	Approximate Fuse Size	
					Diam. (mm)	Length (mm)
7-CRNR100	250 Volts	100 Amps	0782634507437	5	19.0mm	150.0mm
7-CRNR15	250 Volts	15 Amps	0782634507307	10	14.5mm	51.0mm
7-CRNR20	250 Volts	20 Amps	0782634507321	10	14.5mm	51.0mm
7-CRNR25	250 Volts	25 Amps	0782634507338	10	14.5mm	51.0mm
7-CRNR30	250 Volts	30 Amps	0782634507345	10	14.5mm	51.0mm
7-CRNR3	250 Volts	35 Amps	0782634507352	10	20.5mm	76.5mm
7-CRNR40	250 Volts	40 Amps	0782634507369	10	20.5mm	76.5mm
7-CRNR45	250 Volts	45 Amps	0782634507376	10	20.5mm	76.5mm
7-CRNR50	250 Volts	50 Amps	0782634507383	10	20.5mm	76.5mm
7-CRNR60	250 Volts	60 Amps	0782634507390	10	20.5mm	76.5mm
7-CRNR70	250 Volts	70 Amps	0782634507406	5	19.0mm	150.0mm
7-CRNR80	250 Volts	80 Amps	0782634507413	5	19.0mm	150.0mm
7-CRNR90	250 Volts	90 Amps	0782634507420	5	19.0mm	150.0mm